


# THICK FILM (ANTI SURGE <ANTI SULFURATION>)



## SG73-RT | Surge Current Flat Chip Resistors (Anti Sulfuration)

Flat Chip Resistors



Coating color: Wine red

### Features

- Excellent anti-sulfuration characteristic due to using high sulfuration-proof inner top electrode material.
- Superior to RK73 series chip resistors in surge withstanding voltage and pulse withstanding voltage.
- Suitable for both reflow and flow solderings.
- Products with lead free termination meet EU-RoHS requirements. EU-RoHS regulation is not intended for Pb-glass contained in electrode, resistor element and glass.
- AEC-Q200 qualified.


### Applications

- Car electronics, Power supply, Industrial robot

### Reference Standards

IEC 60115-8  
JIS C 5201-8  
EIAJ RC-2134C

### Construction



### Dimensions

Type (Inch Size Code)	Dimensions (mm)					Weight (g) (1000pcs)
	L±0.2	W	c	d	t±0.1	
1J (0603)	1.6	0.8±0.1	0.3±0.1	0.3±0.1	0.45	2.14
2A (0805)	2.0	1.25±0.1	0.4±0.2	0.3 <sup>+0.2</sup> <sub>-0.1</sub>	0.5	4.54
2B (1206)	3.2	1.6±0.2	0.5±0.3	0.4 <sup>+0.2</sup> <sub>-0.1</sub>	0.6	9.14
2E (1210)		2.6±0.2				15.50
W2H (2010)	5.0	2.5±0.2		0.65±0.15		24.30
W3A (2512)	6.3	3.1±0.2		37.10		

### Type Designation

Example

SG73	2A	R	T	TD	103	K
Product Code	Power Rating	Characteristic	Terminal Surface Material	Taping	Nominal Resistance	Resistance Tolerance
	1J:0.1W 2A:0.125W 2B:0.33W 2E:0.5W W2H:0.75W W3A:1W	R:Anti sulfuration	T:Sn	TP:2mm pitch punch paper TD:4mm pitch punch paper TE:4mm pitch plastic embossed BK:Bulk	3 digits	K:±10% M:±20%

Contact us when you have control request for environmental hazardous material other than the substance specified by EU-RoHS.

For further information on taping, please refer to APPENDIX C on the back pages.

### Ratings

Type	Power Rating	Rated Ambient Temp.	Rated Terminal Part Temp.	T.C.R. (×10 <sup>-6</sup> /K)	Resistance Range (Ω)	Max. Working Voltage	Max. Overload Voltage	Packaging & Q'ty/Reel (pcs)		
					K: ±10% M: ±20% E12			TP	TD	TE
1J	0.1W	70°C	125°C	±400	1~8.2	50V	100V	10,000	5,000	—
					10~1M					
2A	0.125W	70°C	125°C	±400	1~8.2	150V	200V	10,000	5,000	4,000 <sup>※1</sup>
					10~1M					
2B	0.33W	70°C	125°C	±400	1~8.2	200V	400V	—	5,000	4,000 <sup>※1</sup>
					10~1M					
2E	0.5W	70°C	125°C	±400	1~8.2	200V	400V	—	5,000	4,000 <sup>※1</sup>
					10~1M					
W2H	0.75W	70°C	125°C	±400	1~8.2	200V	400V	—	—	4,000
				±200	10~1M					
W3A	1.0W	70°C	125°C	±400	1~8.2	200V	400V	—	—	4,000
					10~1M					

Operating Temperature Range : -55°C ~ +155°C

Rated voltage = √(Power Rating × Resistance value) or Max. working voltage, whichever is lower.


※1 Standard packaging : TD(4mm pitch punch paper)

If any questions arise whether to use the "Rated Ambient Temperature" or the "Rated Terminal Part Temperature" in your usage conditions, please give priority to the "Rated Terminal Part Temperature".


For more details, please refer to "Introduction of the derating curves based on the terminal part temperature" on the beginning of our catalog.

## Derating Curve

Ambient temperature



Terminal part temperature



For resistors operated at an ambient temperature of 70°C or higher, the power shall be derated in accordance with the above derating curve.

When the terminal part temperature of the resistor exceeds the rated terminal part temperature shown above, the power shall be derated according to the derating curve.

※Please refer to "Introduction of the derating curves based on the terminal part temperature" on the beginning of our catalog before use.

## Performance

Test Items	Performance Requirements $\Delta R \pm (\% + 0.1 \Omega)$		Test Methods
	Limit	Typical	
Resistance	Within specified tolerance	—	25°C
T.C.R.	Within specified T.C.R.	—	+25°C / -55°C and +25°C / +125°C
Overload (Short time)	2	0.5	Rated voltage $\times 2.5$ for 5s
Resistance to soldering heat	1	0.75	260°C $\pm 5^\circ\text{C}$ , 10s $\pm 1$ s
Rapid change of temperature	0.5	0.3	-55°C (30min.) / +125°C (30min.) 100 cycles
Moisture resistance	3	0.75	40°C $\pm 2^\circ\text{C}$ , 90%~95%RH, 1000h 1.5h ON/0.5h OFF cycle
Endurance at 70°C or rated terminal part temperature	3	0.75	70°C $\pm 2^\circ\text{C}$ or rated terminal part temperature $\pm 2^\circ\text{C}$ 1000h 1.5h ON/0.5h OFF cycle
High temperature exposure	1	0.3	+155°C, 1000h
Sulfuration test	5	0.2	Soaked in industrial oil with sulfur substance 3.5% contained 105°C $\pm 3^\circ\text{C}$ 500h

Please refer to conventional products for characteristic data such as temperature rise.

## Precautions for Use

- The substrate of chip resistors is alumina. Cracks may occur at the connection of solder (solder fillet portion) due to the difference of the coefficient of thermal expansion from a mounting board when heat stress like heat cycle, etc. are repeatedly given to them. Care should be taken to the occurrence of the cracks when the change in ambient temperature or ON/OFF of load is repeated, especially when large types of W2H/W3A which have large thermal expansion and also self heating. By general temperature cycle test using glass-epoxy (FR-4) boards under the maximum/minimum temperatures of operating temperature range, the crack does not occur easily in the types of 1J~2E, but the crack tends to occur in the types of W2H/W3A. The occurrence of the crack by heat stress may be influenced by the size of a pad, solder volume, heat radiation of mounting board etc., so please pay careful attention to designing when a big change in ambient temperature and conditions for use like ON/OFF of load can be assumed.