


THICK FILM (ANTI SULFURATION)




RK73B·RK73H·RK73Z-RT Flat Chip Resistors (Anti Sulfuration)



Coating Color :

Black (RK73B 1F, 1H, 1E, 1J, 2A, 2B, 2E, W2H, W3A, W3A2)
 (RK73H 1F, 1H) (RK73Z 1J, 2A, 2B, 2E, W2H, W3A)
 Blue (RK73H 1E, 1J, 2A, 2B, 2E, W2H, W3A, W3A2)
 Green (RK73Z 1H, 1E)

Construction



Dimensions

Type (Inch Size Code)	Dimensions (mm)					Weight(g) (1000pcs)
	L	W	c	d	t	
1F (01005)	0.4±0.02	0.2±0.02	0.1±0.03	0.11±0.03	0.13±0.02	0.04
1H (0201)	0.6±0.03	0.3±0.03	0.1±0.05	0.15±0.05	0.23±0.03	0.14
1E (0402)	1.0 ^{+0.1} _{-0.05}	0.5±0.05	0.2±0.1	0.25 ^{+0.05} _{-0.1}	0.35±0.05	0.68
1J (0603)	1.6±0.2	0.8±0.1	0.3±0.1	0.3±0.1	0.45±0.1	2.14
2A (0805)	2.0±0.2	1.25±0.1	0.4±0.2	0.3 ^{+0.2} _{-0.1}	0.5±0.1	4.54
2B (1206)	3.2±0.2	1.6±0.2	0.5±0.3	0.4 ^{+0.2} _{-0.1}	0.6±0.1	9.14
2E (1210)		2.6±0.2		15.5		
W2H (2010)	5.0±0.2	2.5±0.2	0.65±0.15	0.6±0.1	0.6±0.1	24.3
W3A (2512)	6.3±0.2	3.1±0.2				37.1
W3A2 (2512) ^{B1}						

*1 Exemption RK73Z

Features

- Excellent anti-sulfuration characteristic due to using high sulfuration-proof inner top electrode material.
- Excellent heat resistance and weather resistance are ensured by the use of metal glaze thick film.
- High stability and high reliability with the triple-layer structure of electrode.
- Suitable for both flow and reflow solderings.
- This products meet EU-RoHS requirements. EU-RoHS regulation is not intended for Pb-glass contained in electrode, resistor element and glass.
- AEC-Q200 Qualified. (Exemption 1F)

Applications

- Car electronics, Power supply, Industrial robot

Reference Standards

IEC 60115-8
 JIS C 5201-8
 EIAJ RC-2134C

Type Designation


Example

RK73H	2A	RT	TD	1002	F
Product Code	Power Rating	Terminal Surface Material	Taping	Nominal Resistance	Resistance Tolerance
RK73B RK73H	1F: 0.03W 1H: 0.05W 1E: 0.1W 1J: 0.1W 0.125W 2A: 0.25W 2B: 0.25W 2E: 0.5W W2H: 0.75W W3A: 1W W3A2: 2W	RT : Sn	TX: 4mm width-1mm pitch plastic embossed TBL·TC: 2mm pitch press paper TPL·TP: 2mm pitch punch paper TD: 4mm pitch punch paper TE: 4mm pitch plastic embossed BK: Bulk	RK73B: 3 digits RK73H: 4 digits	D: ±0.5% F: ±1% G: ±2% J: ±5%
RK73Z	2A	RT	TD		
Product Code	Current Rating	Terminal Surface Material	Taping		
RK73Z	1H: 0.5A 1E: 1A 1J: 1A 2A: 2A 2B: 2A 2E: 2A W2H: 2A W3A: 2A	RT : Sn	TC: 2mm pitch press paper TPL·TP: 2mm pitch punch paper TD: 4mm pitch punch paper TE: 4mm pitch plastic embossed BK: Bulk		


Contact us when you have control request for environmental hazardous material other than the substance specified by EU-RoHS. For further information on taping, please refer to APPENDIX C on the back pages.

Derating Curve


RK73B · RK73H · RK73Z-RT
Ambient temperature



RK73B · RK73H · RK73Z-RT
Terminal part temperature



RK73B · RK73H-RT
Terminal part temperature W3A2



For resistors operated at an ambient temperature of 70°C or higher, the power (for RK73B, RK73H) or a current rating (for RK73Z) shall be derated in accordance with the above derating curve.

When the terminal part temperature of the resistor exceeds the rated terminal part temperature shown above, the power shall be derated according to the derating curve.

*Please refer to "Introduction of the derating curves based on the terminal part temperature" on the beginning of our catalog before use.

Ratings

RK73B, RK73H

Type	Power Rating	Rated Ambient Temp.	Rated Terminal Part Temp.	T.C.R. (×10 ⁻¹ /K)	Resistance Range (Ω)				Max. Working Voltage	Max. Overload Voltage	Packaging & Q'ty/Reel (pcs)						
					RK73H		RK73B				TX	TBL	TC·TCM	TPL·TP	TD	TE	
					D: ±0.5% E24·E96	F: ±1% E24·E96	G: ±2% E24	J: ±5% E24									
1F	0.03W	70°C	—	—	±200	—	100k~2M ^{※2}	100k~1M	100k~10M	20V	30V	40,000	20,000	—	—	—	—
					±250	—	10~91k ^{※2}	10~91k	10~91k								
					0~±300	—	1~9.1	1~9.1	1~9.1								
1H	0.05W	70°C	125°C	—	±200	100~100k	100~1M	—	100~1M	25V	50V	—	—	—	—	—	—
					±300	—	10~97.6	—	—								
					±100	100~1M	10~1M	—	10~91								
1E	0.1W	70°C	125°C	—	±200	—	1.02M~10M	10~10M	1~10M	75V	100V	—	—	—	—	—	—
					±100	1.02k~1M	1.02k~1M	—	—								
					±200	—	1.02M~10M	1.1k~10M	1.1k~10M								
1J	0.1W 0.125W	70°C	125°C	—	±200	—	1.02M~10M	1.1k~10M	1.1k~10M	150V	200V	—	—	—	—	—	—
					±100	100~1k	10~1k	—	—								
					±200	—	10~1k	1~1k	—								
2A	0.25W	70°C	125°C	—	±100	100~1M	10~1M	—	—	200V	400V	—	—	—	—	—	—
					±200	—	1.02M~10M	10~10M	1~10M								
					±100	100~1M	10~1M	—	—								
2B	0.25W	70°C	125°C	—	±200	—	1.02M~10M	10~10M	1~10M	200V	400V	—	—	—	—	—	—
					±100	100~1M	10~1M	—	—								
					±200	—	10~1M	—	—								
2E	0.5W	70°C	125°C	—	±200	—	10~1M	10~1M	1~1M	200V	400V	—	—	—	—	—	—
					±100	10~1M	10~1M	—	—								
					±200	—	1~9.76	1~10M	1~10M								
W2H	0.75W	70°C	125°C	—	±100	10~1M	10~1M	—	—	200V	400V	—	—	—	—	—	—
					±200	—	1.02M~10M	10~10M	1~10M								
					±100	10~1M	10~1M	—	—								
W3A	1W	70°C	125°C	—	±200	—	1.02M~10M	10~10M	1~10M	200V	400V	—	—	—	—	—	—
					±100	10~1M	10~1M	—	—								
					±200	—	1.02M~10M	10~10M	1~10M								
W3A2	2W	—	95°C	—	±100	10~1M	10~1M	—	—	200V	400V	—	—	—	—	—	—
					±200	—	1.02M~10M	10~10M	1~10M								
					±100	10~1M	10~1M	—	—								

Operating Temperature Range : -55°C ~ +125°C (1F), -55°C ~ +155°C (1H·1E·1J·2A·2B·2E·W2H·W3A·W3A2)

※2 The nominal resistance value for RK73H1F (F:±1%) is E24.

Rated voltage = √(Power Rating × Resistance value or Max. working voltage, whichever is lower).

If any questions arise whether to use the "Rated Ambient Temperature" or the "Rated Terminal Part Temperature" in your usage conditions, please give priority to the "Rated Terminal Part Temperature". For more details, please refer to "Introduction of the derating curves based on the terminal part temperature" on the beginning of our catalog.

While using under high power, the temperature of the product may increase depending on the condition of heat dissipation from PCB.

Be sure to check the terminal part temperature as well as precautions to use on delivery specifications before use.

RK73Z

Type	Rated Ambient Temperature	Rated Terminal Part Temp.	Resistance	Current Rating	Max. Overload Current	Operating Temp. Range	Packaging & Q'ty/Reel (pcs)			
							TC·TCM	TPL·TP	TD	TE
1H	70°C	125°C	100mΩmax.	0.5A	1A	-55°C ~ +155°C	TC : 10,000	—	—	—
1E	70°C	125°C	50mΩmax.	1A	2A		TCM: 15,000	—	—	—
							—	TPL: 20,000	—	—
							—	TP : 10,000	—	—
2A	70°C	125°C	50mΩmax.	2A	10A		—	TP : 10,000	5,000	4,000
2B							—	—	5,000	4,000
2E							—	—	5,000	4,000
W2H							—	—	—	4,000
W3A							—	—	—	4,000

Performance

Test Items	RK73H, RK73B		RK73Z		Test Methods
	Performance Requirements ΔR± (%+0.1 Ω)		Performance Requirements		
	Limit	Typical	Limit	Typical	
Resistance	Within specified tolerance	—	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	R ≤ 90mΩ : 1H R ≤ 40mΩ : others	25°C
T.C.R.	Within specified T.C.R.	—	—	—	+25°C / -55°C and +25°C / +125°C
Overload (Short time)	2	1 : 1F 0.8 : others	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	R ≤ 90mΩ : 1H R ≤ 40mΩ : others	RK73B, RK73H : Rated voltage × 2.5 for 5s (1E, 2B, W3A2: Rated voltage × 2 for 5s) Max. overload current, 5s
Resistance to soldering heat	1 : 10 Ω ≤ R ≤ 1M Ω 3 : R < 10 Ω, R > 1M Ω	1 : R < 10 Ω, R > 1M Ω 0.5 : others	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	R ≤ 90mΩ : 1H R ≤ 40mΩ : others	260°C ± 5°C, 10s ± 1s
Rapid change of temperature	1 : 1F 0.5 : others	0.5 : 1F 0.3 : others	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	R ≤ 90mΩ : 1H R ≤ 40mΩ : others	-55°C (30min.) / +125°C (30min.) 100 cycles
Moisture resistance	2 : 1J, 2A, 2B 3 : others	0.75 : 1J, 2A, 2B 1.5 : 1F 1 : others	R ≤ 150mΩ : 1H R ≤ 100mΩ : others	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	40°C ± 2°C, 90% ~ 95%RH, 1000h 1.5h ON/0.5h OFF cycle
Endurance at 70°C or rated terminal part temperature	2 : 1J, 2A, 2B 3 : others	0.75 : 1J, 2A, 2B 1 : others	R ≤ 150mΩ : 1H R ≤ 100mΩ : others	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	70°C ± 2°C or rated terminal part temperature ± 2°C 1000h 1.5h ON/0.5h OFF cycle
High temperature exposure	1	0.5	R ≤ 150mΩ : 1H R ≤ 100mΩ : others	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	+125°C, 1000h : 1F +155°C, 1000h : 1H, 1E, 1J, 2A, 2B, 2E, W2H, W3A, W3A2
Sulfuration test	5	0.3 : 1F, 1H 0.2 : others	R ≤ 150mΩ : 1H R ≤ 100mΩ : others	R ≤ 100mΩ : 1H R ≤ 50mΩ : others	Soaked in industrial oil with sulfur substance 3.5% contained 105°C ± 3°C 500h

Please refer to conventional products for characteristic data such as temperature rise.

Precautions for Use

- The substrate of chip resistors is alumina. Cracks may occur at the connection of solder (solder fillet portion) due to the difference of the coefficient of thermal expansion from a mounting board when heat stress like heat cycle, etc. are repeatedly given to them. Care should be taken to the occurrence of the cracks when the change in ambient temperature or ON/OFF of load is repeated, especially when large types of W2H/W3A/W3A2 which have large thermal expansion and also self heating. By general temperature cycle test using glass-epoxy(FR-4) boards under the maximum/minimum temperatures of operating temperature range, the crack does not occur easily in the types of 1F~2E, but the crack tends to occur in the types of W2H/W3A/W3A2. The occurrence of the crack by heat stress may be influenced by the size of a pad, solder volume, heat radiation of mounting board etc., so please pay careful attention to designing when a big change in ambient temperature and conditions for use like ON/OFF of load can be assumed.
- Care should be taken that RK73B1F and RK73H1F may be damaged when static electricity occurs and is applied in the equipment assembly process.